

MATERIAL SAFETY DATA SHEET
 FOR COATINGS, RESINS AND RELATED MATERIALS
 (Approved by US Dept. Of Labor Essentially Similar to Forms OSHA 20)

Date of Prep 6/5/1999 (Rev. 8/5/99)

SECTION 1

Manufacturers Name

KM COATINGS MFG., INC.
 1719 W. BUCHANAN ST.
 PHOENIX, AZ 85007
 602-253-1168

Product Class

URETHANE ACRYLIC-LATEX EXTERIOR COATING

Manufacturers Code Identification

Trade Name

URE-FLEX

SECTION 11 - Hazardous Ingredients

<u>Ingredient</u>	<u>Percent</u>	<u>PPM</u>	<u>TLV</u>		<u>LEL</u>	<u>Vapor Pressure</u>
				<u>mg/M3</u>		
ETHYLENE GLYCOL CAS#107-21-1	2.00%	50			3.2%	.10mmHg

SECTION III - PHYSICAL DATA

Boiling Range 379-401 Vapor Density (X) Heavier () Lighter Than Air
 Evaporation Rate () Faster (x) Slower, Than Ether Percent Volatile 100.0% Weight Per Gallon 8.25#
 By VOI By Volume

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY n/a Flash Point 232 LEL

Extinguishing Media

CO₂, FOAM, & DRY CHEMICAL

Unusual Fire and Explosion Hazards

Closed Containers May Explode When Exposed to
 Extreme Heat. Products of Combustion May be Toxic

Special Fire Fighting Procedures Wear Self Contained Breathing Apparatus

Water May be Used to Cool Closed Containers. High Pressure Stream will Spread Fire.

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value	None Established
Effects of Over Exposure	Inhalation of Vapors in Poorly Ventilated May Cause Headache or Dizziness, Skin Absorption Should not be a Problem. Direct Contact May Cause Eye Irritation.
Emergency First Aid Procedure	Remove to Fresh Air, Wash Exposed Areas with Soap and Water, Flush Eyes with Copious Amounts of Water if Symptoms Persist, Consult A Physician.

SECTION VI - REACTIVITY DATE

Stability () Unstable () (X) Stable Conditions to Avoid: None

Incompatibility (Materials to Avoid)

Hazardous Decomposition Products: None

Hazardous Polymerization () May Occur (X) Will Not Occur

Conditions to Avoid: None

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Materials is Released or Spilled: Soak up Spill with Sand or Other Absorbent, Place in Containers. Wash Area.

Waste Disposal Method Dispose in Accordance with Local, State or Federal Regulations

SECTION VIII - SPECIAL PROTECTION INFORMATION

Respiratory Protection:	If Applied by Spraying, Particle Mask Should be Used to Avoid Inhalation of Atomized Paint
Ventilation:	Use with Adequate Ventilation
Protective Gloves:	Rubber Should be Used
Eye Protection:	Safety Glasses or Goggles
Other Protective Equipment:	N/A

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be Taken in Handling and Storage

Store in Cool Place

Other Precautions:

Keep out of Reach of Children
Avoid Contact with Skin or Clothing
Keep Container Closed
Wash Thoroughly After Using